

P/N AN5C61A

Description

Fastener Length: 6-1/4", Thread: 1/4-24, Thread Length: 5-63/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN5C61A

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-298-3118

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N AN5C61A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	5.672 Inches Minimum And 6.704 Inches Maximum
Fastener Length:	6.203 Inches Minimum And 6.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	5.672 Inches Minimum And 6.704 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN5C61A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.