



Military-Fasteners.com

P/N AN5DD10A

Description

Fastener Length: 1-3/32", Thread: 1/4-24, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5DD10A
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-151-1068
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts



* See page 2 for technical characteristics

P/N AN5DD10A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.532 Inches Minimum
Fastener Length:	1.094 Inches Nominal
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.562 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy Overall
Material Document And Classification:	Qq-a-267 Fed Spec 1st Material Response Overall Or Qq-a-268 Fed Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 2nd Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN5DD10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.