

P/N AN5H13A

Description

length: 1-15/32", grip: 15/16", thread: 5/16-24, cadmium plated steel, undrilled shank, drilled head, AN5 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN5H13A

Minimum Qty (MOQ): 10

NSN: 5306-00-182-2030

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN5H13A Specifications

Thread Length: 1.469 Inches Nominal Head Style: Hexagon Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Hole Diameter: 0.1312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: Hole Type: 0rilled Features Provided: Finished Head Thread Quantity Per Inch: 4 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material Document And Classification: Mil-6812 Mil Spec All Material Responses Overall Surface Treatment: Camium Overall And Chromate Overall Surface Treatment Document And Overall Or Steel Spec All Treatment Responses Overall Surface Treatment Document And Overall Or Steel Spec All Treatment Responses Overall Overall Or Steel Spec All Treatment Responses Overall		
Fastener Length: 1.469 Inches Nominal Head Style: Hexagon Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Nominal Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8730 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2.class 3 Fed Spec All Treatment Responses Overall	Thread Class:	Al
Head Style: Hexagon Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Hole Dlameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.938 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material Document And Classification: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8140 Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416.type 2,class 3 Fed Spec All Treatment Responses Overall	Thread Length:	0.531 Inches Minimum
Head Height: 0.172 Inches Minimum And 0.204 Inches Maximum Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hardness Rating: 125000 Pounds Per Square Inch Hexagon Flats Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment Document And Classification: Q-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Fastener Length:	1.469 Inches Nominal
Width Between Flats: 0.490 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Nominal Thread Diameter: 0.312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Head Style:	Hexagon
Hole Diameter: 0.070 Inches Nominal Nominal 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1	Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Nominal Thread Diameter: 0.312 Inches Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 44 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 46.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Grip Length: 0.938 Inches Nominal Hole Quantity: 1 Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hole Diameter:	0.070 Inches Nominal
Hole Quantity: Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 46.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Material: Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall Classification:	Nominal Thread Diameter:	0.312 Inches
Hole Type: Drilled Features Provided: Finished Head Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Class 3 Fed Spec All Treatment Responses Overall	Grip Length:	0.938 Inches Nominal
Features Provided: Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hole Quantity:	1
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Minimum Tensile Strength: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Features Provided:	Finished Head
Hardness Rating: Hole Configuration Style: Hexagon Flats Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	24
Hole Configuration Style: Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8745 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Mil-b-6812 Mil Spec All Material Responses Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Hole Configuration Style:	Hexagon Flats
Surface Treatment: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Classification: Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN5H13A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.