

P/N AN5H4A

Military-Fasteners.com

Description

length: 19/32", grip: 1/16", thread: 5/16-24, cadmium plated steel undrilled shank, drilled head

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	AN5H4A
Minimum Qty (MOQ):	20
NSN:	5306-00-182-2023
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN5H4A Specifications

Intread Direction:Joint Construction:Thread Direction:Right-handThread Length:0.532 Inches MinimumFastener Length:0.594 Inches NominalHead Style:HexagonHead Style:NexagonHead Height:0.172 Inches Minimum And 0.204 Inches MaximumWidth Between Flats:0.490 Inches Minimum And 0.502 Inches MaximumHole Diameter:0.470 Inches NominalNominal Thread Diameter:0.312 Inches0.070 Inches NominalNominalHole Quantity:11Onde Inches NominalHole Type:NominalHole Quantity:11Store Store S	Thread Class:	За
Thread Length:0.33 Inches MinimumFastener Length:0.594 Inches NominalHead Style:HexagonHead Height:0.172 Inches Minimum And 0.204 Inches MaximumHead Height:0.490 Inches Minimum And 0.202 Inches MaximumWidth Between Flats:0.490 Inches Minimum And 0.502 Inches MaximumNominal Thread Diameter:0.070 Inches NominalSorip Length:0.062 Inches NominalHole Quantity:0.062 Inches NominalHole Quantity:1Hole Strength:0.062 Inches NominalHole Strength:0.062 Inches NominalHole Ougantity:1Hole Strength:0.062 Inches NominalHole Strength:0.062 Inches Nominal<		
Fastener Length:0.594 Inches NominalHead Style:HexagonHead Height:0.172 Inches Minimum And 0.204 Inches MaximumHead Height:0.172 Inches Minimum And 0.502 Inches MaximumWidth Between Flats:0.490 Inches NominalNominal Thread Diameter:0.070 Inches NominalSominal Thread Diameter:0.312 InchesGrip Length:0.602 Inches NominalHole Quantity:1Hole Type:0.602 Inches NominalHole Type:DiriledFeatures Provided:Ninished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardenes Rating:6.0. Rockwell C Minimum Overall And 32.0. Rockwell C Maximum OverallHole Configuration Style:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-beatz All Kersponse OverallRurface Treatment:Gadmium Overall And Chromate OverallRurface Treatment And Classification:Gadmium Overall And Chromate Overall		-
Head Style:HexagonHead Height:0.172 Inches Minimum And 0.204 Inches MaximumWidth Between Flats:0.490 Inches Minimum And 0.502 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.312 InchesOnfol Engenter:0.062 Inches NominalHole Quantity:0.062 Inches NominalHole Quantity:1Hole Type:DrilledFactures Provided:Finished HeadThread Quantity Per Inch:24Uston Pounds Per Square Inch25000 Pounds Per Square InchHole Configuration Style:Hexagon FlatsMaterial Document And Classification:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Com	Thread Length:	0.532 Inches Minimum
Head Height:0.172 Inches Minimum And 0.204 Inches MaximumWidth Between Flats:0.490 Inches Minimum And 0.502 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.312 InchesOminal Thread Diameter:0.312 InchesGrip Length:0.662 Inches NominalHole Quantity:1Hole Type:DrilledFeatures Provided:Inished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHole Configuration Style:Hexagon FlatsMaterial Document And Classification:Mil-See All Material Responses OverallSurface Treatment Document And Classification:Mil-See Alg Spe 13th Treatment Response Overall	Fastener Length:	0.594 Inches Nominal
Width Between Flats:0.490 Inches Mininum And 0.502 Inches MaximumHole Diameter:0.070 Inches NominalNominal Thread Diameter:0.312 InchesGrip Length:0.062 Inches NominalHole Quantity:1Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:24US00 Pounds Per Square Inch15000 Pounds Per Square InchHole Configuration Style:0.602 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Nie-Seal Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-be812 Mil Spec All Material Responses OverallSurface Treatment Document AndCadmium Overall And Chromate OverallSurface Treatment Document Andp-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Head Style:	Hexagon
Hole Diameter:0.070 Inches NominalNominal Thread Diameter:0.312 InchesGrip Length:0.062 Inches NominalHole Quantity:1Hole Type:DrilledFeatures Provided:Inished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHole Configuration Style:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHote Configuration Style:Hexagon FlatsMaterial Document And Classification:Mib-6812 Mil Spec All Material Responses OverallSurface Treatment Document And Classification:Mib-cgas 3 Fed Spec 13th Treatment Response Overall	Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Nominal Thread Diameter:0.312 InchesGrip Length:0.662 Inches NominalHole Quantity:1Hole Type:DrilledFeatures Provided:Inished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHole Configuration Style:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHote Configuration Style:tele Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-be6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallS	Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Grip Length:0.062 Inches NominalHole Quantity:1Hole Type:DilledFeatures Provided:Finished HeadThread Quantity Per Inch:2Minimum Tensile Strength:15000 Pounds Per Square InchHole Configuration Style:6.0.8 cckwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Heagon FlatsMaterial Document And Classification:Mil-be812 Mil Material Responses OverallSurface Treatment:Gadinum Overall And AlchormateSurface Treatment And Classification:Mil-be812 Step Step Step Step Step Step Step Step	Hole Diameter:	0.070 Inches Nominal
Hole Quantity:1Hole Type:DrilledFeatures Provided:Finished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 9735 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:0-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Nominal Thread Diameter:	0.312 Inches
Hole Type:DrilledFeatures Provided:Finished HeadFinished HeadFinished HeadThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8730 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-be812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:op-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Grip Length:	0.062 Inches Nominal
Features Provided:Finished HeadFread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall O	Hole Quantity:	1
Thread Quantity Per Inch:24Thread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallQ-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Hole Type:	Drilled
Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallQ-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Features Provided:	Finished Head
Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8736 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Overall And Chromate Overall	Thread Quantity Per Inch:	24
Hole Configuration Style:Hexagon FlatsMaterial:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Overall Overall O	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:Overall Or Steel Comp 4140 OverallMaterial Document And Classification:Mil-b-6812 Mil Spec All Material Responses OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Hole Configuration Style:	Hexagon Flats
Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Material:	
Surface Treatment Document And Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall Classification: Description:	Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Classification: Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf		Q-p-416,type 2,class 3 Fed Spec 13th Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN5H4A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.