

Description

length: 2-37/64", grip: 1-15/16", thread: 3/8-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN624
Minimum Qty (MOQ):	20
NSN:	5306-00-167-3690
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN6-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.640 Inches Minimum
Fastener Length:	2.578 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.938 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.376 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.