

Description

Fastener Length: 6-5/16", Thread: 3/8-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN662
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-167-3720
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN6-62 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.640 Inches Minimum
Fastener Length:	6.328 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	5.688 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	6.126 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6050 Mil Spec Single Material Response Overall Or Mil-s-6098 Mil Spec Single Material Response Overall Or Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-8695 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6-62> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.