

## Description

Hole Diameter: 1/4", Thread Size: 1/8", Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN66510R
Minimum Qty (MOQ):	5
NSN:	5340-00-530-5354
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	094140, Clevises Iron / Steel

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN665-10R Specifications

<b>Thread Class:</b>	3a Rod Connection
<b>Thread Direction:</b>	Right-hand Rod Connection
<b>Thread Length:</b>	0.203 Inches Minimum Rod Connection And 0.297 Inches Maximum Rod Connection
<b>Shank Length:</b>	0.673 Inches Minimum And 0.703 Inches Maximum
<b>Hole Diameter:</b>	0.190 Inches Minimum And 0.192 Inches Maximum
<b>Shank Diameter:</b>	0.250 Inches Minimum And 0.260 Inches Maximum
<b>Overall Width:</b>	0.255 Inches Minimum And 0.265 Inches Maximum
<b>End Radius:</b>	0.188 Inches Nominal
<b>Metallic Hardness Rating:</b>	26.0 Minimum Rockwell C And 31.0 Maximum Rockwell C
<b>Fork Span Width:</b>	0.109 Inches Minimum And 0.119 Inches Maximum
<b>Securing Pin Hole Diameter:</b>	0.046 Inches Nominal
<b>Distance From Center Of Securing Pin Hole To Rod End:</b>	0.313 Inches Nominal
<b>Distance From Pivot Pinhole Center To Rod Connection End:</b>	1.298 Inches Minimum And 1.328 Inches Maximum
<b>Fork Arm Thickness:</b>	0.068 Nominal Mils And 0.073 Nominal Centimeters
<b>Fork Depth:</b>	0.375 Inches Nominal
<b>Nominal Thread Size:</b>	0.138 Inches Rod Connection
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Zinc Overall
<b>Style Designator:</b>	Clevis
<b>Thread Series Designator:</b>	Unf Rod Connection

## How to Order

Order this clevis rod end from our inventory online by visiting <https://military-fasteners.com/rod+ends/clevis+rod+ends/AN665-10R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.