

Description

threaded - thread: 1/4-28, hole diameter: 0.250

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN66534R
Minimum Qty (MOQ):	1
NSN:	5340-00-530-5357
National Motor Freight:	094140, Clevises Iron / Steel

NO IMAGE
AVAILABLE

P/N AN665-34R Specifications

Thread Class:	3b Rod Connection
Thread Direction:	Right-hand Rod Connection
Thread Length:	0.391 Inches Minimum Rod Connection And 0.485 Inches Maximum Rod Connection
Shank Length:	0.923 Inches Minimum And 0.953 Inches Maximum
Hole Diameter:	0.250 Inches Minimum And 0.253 Inches Maximum
Shank Diameter:	0.375 Inches Minimum And 0.385 Inches Maximum
Overall Width:	0.433 Inches Minimum And 0.448 Inches Maximum
End Radius:	0.313 Inches Nominal
Metallic Hardness Rating:	26.0 Minimum Rockwell C And 31.0 Maximum Rockwell C
Fork Span Width:	0.203 Inches Minimum And 0.213 Inches Maximum
Securing Pin Hole Diameter:	0.046 Inches Nominal
Distance From Center Of Securing Pin Hole To Rod End:	0.500 Inches Nominal
Distance From Pivot Pinhole Center To Rod Connection End:	1.798 Inches Minimum And 1.828 Inches Maximum
Fork Arm Thickness:	0.110 Nominal Mils And 0.123 Nominal Centimeters
Fork Depth:	0.625 Inches Nominal
Hole Shape:	Round
Nominal Thread Size:	0.250 Inches Rod Connection
Material:	Steel Overall
Style Designator:	Clevis
Thread Series Designator:	Unf Rod Connection

How to Order

Order this clevis rod end from our inventory online by visiting <https://military-fasteners.com/rod+ends/clevis+rod+ends/AN665-34R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.