

**Description**

threaded - thread: 1/4-28, hole diameter: 0.250

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN66534R
Minimum Qty (MOQ):	1
NSN:	5340-00-530-5357
National Motor Freight:	094140, Clevises Iron / Steel

NO IMAGE  
AVAILABLE

## P/N AN665-34R Specifications

<b>Thread Class:</b>	3b Rod Connection
<b>Thread Direction:</b>	Right-hand Rod Connection
<b>Thread Length:</b>	0.391 Inches Minimum Rod Connection And 0.485 Inches Maximum Rod Connection
<b>Shank Length:</b>	0.923 Inches Minimum And 0.953 Inches Maximum
<b>Hole Diameter:</b>	0.250 Inches Minimum And 0.253 Inches Maximum
<b>Shank Diameter:</b>	0.375 Inches Minimum And 0.385 Inches Maximum
<b>Overall Width:</b>	0.433 Inches Minimum And 0.448 Inches Maximum
<b>End Radius:</b>	0.313 Inches Nominal
<b>Metallic Hardness Rating:</b>	26.0 Minimum Rockwell C And 31.0 Maximum Rockwell C
<b>Fork Span Width:</b>	0.203 Inches Minimum And 0.213 Inches Maximum
<b>Securing Pin Hole Diameter:</b>	0.046 Inches Nominal
<b>Distance From Center Of Securing Pin Hole To Rod End:</b>	0.500 Inches Nominal
<b>Distance From Pivot Pinhole Center To Rod Connection End:</b>	1.798 Inches Minimum And 1.828 Inches Maximum
<b>Fork Arm Thickness:</b>	0.110 Nominal Mils And 0.123 Nominal Centimeters
<b>Fork Depth:</b>	0.625 Inches Nominal
<b>Hole Shape:</b>	Round
<b>Nominal Thread Size:</b>	0.250 Inches Rod Connection
<b>Material:</b>	Steel Overall
<b>Style Designator:</b>	Clevis
<b>Thread Series Designator:</b>	Unf Rod Connection

## How to Order

Order this clevis rod end from our inventory online by visiting <https://military-fasteners.com/rod+ends/clevis+rod+ends/AN665-34R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.