

Description

thread: 5/16-24, hole diameter: 0.313", threaded, AN665 series rod end

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | AN66546R |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5340-00-205-5812 |
| ECCN: | EAR99 |
| National Motor Freight: | 094140, Clevises Iron / Steel |



* See page 2 for technical characteristics

P/N AN665-46R Specifications

| | |
|--|---|
| Thread Class: | 3a Rod Connection |
| Thread Direction: | Right-hand Rod Connection |
| Thread Length: | 0.516 Inches Minimum Rod Connection And 0.610 Inches Maximum Rod Connection |
| Shank Length: | 0.922 Inches Minimum And 0.952 Inches Maximum |
| Hole Diameter: | 0.313 Inches Minimum And 0.316 Inches Maximum |
| Shank Diameter: | 0.438 Inches Minimum And 0.448 Inches Maximum |
| Overall Width: | 0.495 Inches Minimum And 0.510 Inches Maximum |
| End Radius: | 0.344 Inches Nominal |
| Metallic Hardness Rating: | 26.0 Minimum Rockwell C And 31.0 Maximum Rockwell C |
| Fork Span Width: | 0.203 Inches Minimum And 0.213 Inches Maximum |
| Securing Pin Hole Diameter: | 0.046 Inches Nominal |
| Distance From Center Of Securing Pin Hole To Rod End: | 0.625 Inches Nominal |
| Distance From Pivot Pinhole Center To Rod Connection End: | 1.860 Inches Minimum And 1.890 Inches Maximum |
| Fork Arm Thickness: | 0.141 Inches Minimum And 0.153 Inches Maximum |
| Fork Depth: | 0.656 Inches Nominal |
| Nominal Thread Size: | 0.312 Inches Rod Connection |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Style Designator: | Clevis |
| Thread Series Designator: | Unf Rod Connection |

How to Order

Order this clevis rod end from our inventory online by visiting <https://military-fasteners.com/rod+ends/clevis+rod+ends/AN665-46R> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.