



★ FASTENERS

Military-Fasteners.com

P/N AN6C15A

Description

length: 1-45/64", grip: 1-1/16", thread: 3/8-24, corrosion resistant steel, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN6C15A
Minimum Qty (MOQ):	5
NSN:	5306-00-582-9589
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN6C15A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.641 Inches Minimum
Fastener Length:	1.703 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.062 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-770 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6C15A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.