

Description

Length: 2-9/16", Thread: 3/8-24, Thread Length: 5/8", AN6 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN6C24 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-582-8742 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN6C24 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.640 Inches Minimum |
| Fastener Length: | 2.578 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.938 Inches Nominal |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.376 Inches Nominal First Hole |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Qq-s-770 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6C24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.