

**Description**

Fastener Length: 2-55/64", Thread: 3/8-24, Thread Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN6C26A                                   |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5306-00-582-6901                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN6C26A Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.609 Inches Minimum And 0.687 Inches Maximum                       |
| <b>Fastener Length:</b>                      | 2.812 Inches Minimum And 2.859 Inches Maximum                       |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.203 Inches Minimum And 0.235 Inches Maximum                       |
| <b>Width Between Flats:</b>                  | 0.553 Inches Minimum And 0.565 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>              | 0.375 Inches  |
| <b>Grip Length:</b>                          | 2.172 Inches Minimum And 2.203 Inches Maximum                       |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 125000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Material:</b>                             | Steel Comp 431 Overall  |
| <b>Material Document And Classification:</b> | Mil-s-18732 Mil Spec Single Material Response Overall               |
| <b>Surface Treatment:</b>                    | Passivate Overall   |
| <b>Thread Series Designator:</b>             | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6C26A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.