

Description

Fastener Length: 5-47/64", Thread: 3/8-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN6C55
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-255-4601
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN6C55 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.609 Inches Minimum And 0.688 Inches Maximum
Fastener Length:	5.687 Inches Minimum And 5.734 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	5.046 Inches Minimum And 5.078 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	5.484 Inches Minimum First Hole And 5.516 Inches Maximum First Hole
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6C55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.