

**Description**

Overall Length: 3/4", Thread: 3/8-24, Thread Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN6C6
Minimum Qty (MOQ):	5
NSN:	5306-00-151-2458
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN6C6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.610 Inches Minimum And 0.687 Inches Maximum
<b>Fastener Length:</b>	0.812 Inches Minimum And 0.859 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.203 Inches Minimum And 0.235 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.172 Inches Minimum And 0.203 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.609 Inches Minimum First Hole And 0.641 Inches Maximum First Hole
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Mil-s-18732 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.