



Military-Fasteners.com

P/N AN6DD25A

Description

Fastener Length: 2-47/64", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------|
| SKU / Model: | AN6DD25A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-151-0792 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013280, Alum Bolts |



* See page 2 for technical characteristics

P/N AN6DD25A Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.641 Inches Minimum |
| Fastener Length: | 2.687 Inches Minimum And 2.734 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 2.047 Inches Minimum And 2.078 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 62000 Pounds Per Square Inch |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Anodize Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6DD25A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.