

Description

Fastener Length: 3-9/16", Thread: 3/8-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN6DD34
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-151-3271
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013280, Alum Bolts

NO IMAGE
AVAILABLE

P/N AN6DD34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.640 Inches Minimum
Fastener Length:	3.578 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.938 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.376 Inches Nominal First Hole
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 1100 Overall Or Aluminum Alloy 2017 Overall Or Aluminum Alloy 2117 Overall Or Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-267 Fed Spec 1st Material Response Overall Or Qq-a-268 Fed Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 1st Material Response Overall Or Mil-w-7986 Mil Spec 2nd Material Response Overall Or Mil-w-7986 Mil Spec 3rd Material Response Overall Or Mil-w-7986 Mil Spec 4th Material Response Overall Or Mil-w-7986 Mil Spec 5th Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6DD34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.