

Description

Fastener Length: 47/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN6DDH5A
Minimum Qty (MOQ):	1
NSN:	5306-00-936-6125
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN6DDH5A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.609 Inches Minimum And 0.687 Inches Maximum
Fastener Length:	0.688 Inches Minimum And 0.734 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.078 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-200 Fed Spec Single Material Response Overall Or Qq-a-225 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6DDH5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.