

**Description**

Fastener Length: 47/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN6DDH5A
Minimum Qty (MOQ):	1
NSN:	5306-00-936-6125
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN6DDH5A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.609 Inches Minimum And 0.687 Inches Maximum
<b>Fastener Length:</b>	0.688 Inches Minimum And 0.734 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.203 Inches Minimum And 0.235 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.078 Inches Maximum
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Qq-a-200 Fed Spec Single Material Response Overall Or Qq-a-225 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Oxide Film Overall And Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6DDH5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.