

Description

length: 1-21/64", grip: 11/16", thread: 3/8-24, cadmium plated steel, undrilled shank, drilled head, AN6 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN6H12A |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5306-00-206-6270 |
| Schedule B: | 7318.15.2095 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN6H12A Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.641 Inches Minimum |
| Fastener Length: | 1.328 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Hole Diameter: | 0.062 Inches Nominal |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.688 Inches Nominal |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6H12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.