

**Description**

length: 2-5/64", grip: 1-7/16", thread: 3/8-24, cadmium plated steel undrilled shank - drilled head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN6H20A                                   |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-00-582-8917                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN6H20A Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.640 Inches Minimum   |
| <b>Fastener Length:</b>                      | 2.078 Inches Nominal   |
| <b>Head Style:</b>                           | Hexagon  |
| <b>Head Height:</b>                          | 0.203 Inches Minimum And 0.235 Inches Maximum  |
| <b>Width Between Flats:</b>                  | 0.553 Inches Minimum And 0.565 Inches Maximum  |
| <b>Hole Diameter:</b>                        | 0.070 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>              | 0.375 Inches   |
| <b>Grip Length:</b>                          | 1.438 Inches Nominal   |
| <b>Hole Quantity:</b>                        | 1  |
| <b>Hole Type:</b>                            | Drilled  |
| <b>Features Provided:</b>                    | Finished Head  |
| <b>Thread Quantity Per Inch:</b>             | 24   |
| <b>Minimum Tensile Strength:</b>             | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                      | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>             | Hexagon Longitudinal Hole  |
| <b>Material:</b>                             | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| <b>Material Document And Classification:</b> | Mil-b-6812 Mil Spec All Material Responses Overall   |
| <b>Surface Treatment:</b>                    | Cadmium Overall And Chromate Overall   |
| <b>Thread Series Designator:</b>             | Unf  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6H20A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.