

**Description**

length: 2-5/64", grip: 1-7/16", thread: 3/8-24, cadmium plated steel undrilled shank - drilled head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN6H20A
Minimum Qty (MOQ):	5
NSN:	5306-00-582-8917
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN6H20A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.640 Inches Minimum
<b>Fastener Length:</b>	2.078 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.203 Inches Minimum And 0.235 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.565 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.438 Inches Nominal
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Hexagon Longitudinal Hole
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-b-6812 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6H20A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.