



Military-Fasteners.com

P/N AN6H25

Description

Fastener Length: 2-11/16", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN6H25
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-206-9577
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN6H25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.641 Inches Minimum
Fastener Length:	2.703 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.062 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.500 Inches Nominal First Hole
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6H25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.