

**Description**

Fastener Length: 4-55/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN6H26A                                   |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-926-5680                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN6H26A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.611 Inches Minimum And 0.687 Inches Maximum  |
| <b>Fastener Length:</b>                               | 4.813 Inches Minimum And 4.859 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.203 Inches Minimum And 0.235 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.553 Inches Minimum And 0.565 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches   |
| <b>Grip Length:</b>                                   | 4.172 Inches Minimum And 4.202 Inches Maximum  |
| <b>Hole Quantity:</b>                                 | 1  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>                      | Hexagon Flats  |
| <b>Material:</b>                                      | Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 3135 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN6H26A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.