

Description

length: 1-15/32", grip: 13/16", thread: 7/16-20, cadmium plated steel undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN713A
Minimum Qty (MOQ):	25
NSN:	5306-00-180-0261
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN7-13A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.656 Inches Minimum
Fastener Length:	1.469 Inches Nominal
Head Style:	Hexagon
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Between Flats:	0.615 Inches Minimum And 0.627 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.812 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN7-13A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.