

Description

length: 2-7/32", grip: 1-9/16", thread: 7/16-20, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN721 |
| Minimum Qty (MOQ): | 4 |
| NSN: | 5306-00-150-9606 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN7-21 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum And 0.703 Inches Maximum |
| Fastener Length: | 2.203 Inches Minimum And 2.250 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.234 Inches Minimum And 0.266 Inches Maximum |
| Width Between Flats: | 0.615 Inches Minimum And 0.627 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.547 Inches Minimum And 1.578 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.031 Inches Minimum First Hole And 2.062 Inches Maximum First Hole |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-5050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN7-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.