

P/N AN7-31A

Military-Fasteners.com

Description

length: 3-7/32", grip: 2-9/16", thread: 7/16-20, cadmium plated steel undrilled shank, AN7 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	AN731A
Minimum Qty (MOQ):	5
NSN:	5306-00-840-0068
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN7-31A Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.657 Inches Minimum
Fastener Length:	3.219 Inches Nominal
Head Style:	Hexagon
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Between Flats:	0.615 Inches Minimum And 0.627 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	2.562 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN7-31A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.