

Description

Fastener Length: 4-19/32", Thread: 7/16-20, Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20073-04-04](#)

SKU / Model:	AN744
Minimum Qty (MOQ):	5
NSN:	5306-00-156-2657
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN7-44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.656 Inches Minimum
Fastener Length:	4.594 Inches Nominal
Head Style:	Hexagon
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Between Flats:	0.615 Inches Minimum And 0.627 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Nominal Thread Diameter:	0.438 Inches
Grip Length:	3.938 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	4.422 Inches Nominal First Hole
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN7-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.