

P/N AN7-45A

Description

length: 4-23/32", grip: 4-1/16", thread: 7/16-20, cadmium plated steel, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN745A

Minimum Qty (MOQ): 5

NSN: 5306-01-234-8293

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N AN7-45A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.656 Inches Nominal
Fastener Length:	4.719 Inches Nominal
Head Style:	Hexagon
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.625 Inches Nominal
Nominal Thread Diameter:	0.438 Inches
Grip Length:	4.062 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN7-45A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.