

## **P/N AN776-4S**

### **Description**

Length: 1-1/2", Thickness: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN7764S

Minimum Qty (MOQ): 1 EA

NSN: 4730-00-274-7020

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN776-4S Specifications

Thread Class:	3a
Thread Class:	3a All Connections
Thread Direction:	Right-hand
Thread Direction:	Right-hand All Connections
Overall Length:	1.531 Inches Nominal
Overall Width:	0.796 Inches Minimum And 0.828 Inches Maximum
Thickness:	0.687 Inches Minimum And 0.697 Inches Maximum
Thread Size:	7/16 In20
Thread Size:	7/16 In20 All Connections
Thread Provision:	Threaded
Thread Provision:	Threaded All Connections
End Item Identification:	Aircraft Application; aircraft Hercules, C-130
Connection Style:	Flared
Connection Style:	Flared All Connections
Bolt Hole Diameter:	0.438 Inches Nominal
Seat Angle In Deg:	37.0
Seat Angle In Deg:	37.0 All Connections
Screw Thread Series Designator:	Unjf
Screw Thread Series Designator:	Unjf All Connections
Seat:	Included
Seat:	Included All Connections
Fluid Connection Quantity:	1
Fluid Connection Quantity:	1 All Connections
Fluid Conveyance Type And Size For Which Designed:	1/4 In. Od Tube
<b>Bolt Hole Flats Serrations:</b>	Provided
Bolt Hole Fluid Passage:	Provided
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Steel, Qq-s-763, Class 347
Material:	Steel Comp 347

Surface Treatment:	Passivate
Style Designator:	1 Fluid Connection
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	88044-an776 Government Standard And 81343-as4875/1 Professional/industrial Association Standard
Specification/standard Data:	81343-as5162 Professional/industrial Association Standard And 81343-as4875/1 Professional/industrial Association Standard

## **How to Order**

Order this fitting from our inventory online by visiting <a href="https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S">https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S">https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S">https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-4S</a> and selecting the