

P/N AN776-5

Description

Length: 1-1/2", Thickness: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN7765

Minimum Qty (MOQ): 1 EA

NSN: 4730-00-277-9759

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN776-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Overall Length:	1.531 Inches Nominal
Overall Width:	0.750 Inches Nominal
Thickness:	0.750 Inches Nominal
Thread Size:	1/2 In20
Thread Provision:	Threaded
Connection Style:	Flared
Bolt Hole Diameter:	0.484 Inches Minimum And 0.502 Inches Maximum
Seat Angle In Deg:	37.0
Screw Thread Series Designator:	Unf
Seat:	Included
Fluid Connection Quantity:	1
Fluid Conveyance Type And Size For Which Designed:	5/16 In. Od Tube
Bolt Hole Flats Serrations:	Provided
Bolt Hole Fluid Passage:	Provided
Material:	Steel, Fed Std 66, Comp 1137
Surface Treatment:	Cadmium And Chromate
Style Designator:	1 Fluid Connection
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 2
Specification/standard Data:	88044-an776- Government Standard And 81343-as4875/1 Professional/industrial Association Standard

How to Order

Order this fitting from our inventory online by visiting https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.