

Description

Length: 1-1/2", Thickness: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN7765D
Minimum Qty (MOQ):	1 EA
NSN:	4730-00-277-9758
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N AN776-5D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Overall Length:	1.531 Inches Nominal
Overall Width:	0.813 Inches Nominal
Thickness:	0.750 Inches Nominal
Thread Size:	1/2 In.-20
Thread Provision:	Threaded
Connection Style:	Flared
Bolt Hole Diameter:	0.500 Inches Nominal
Seat Angle In Deg:	37.0
Screw Thread Series Designator:	Unf
Seat:	Included
Fluid Connection Quantity:	1
Fluid Conveyance Type And Size For Which Designed:	5/16 In. Od Tube
Bolt Hole Flats Serrations:	Provided
Bolt Hole Fluid Passage:	Provided
Material:	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6
Material:	Aluminum Alloy 2014
Surface Treatment:	Anodize
Style Designator:	1 Fluid Connection
Surface Treatment:	Anodized, Mil-a-8625, Type 2, Class 2

How to Order

Order this fitting from our inventory online by visiting <https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.