

**Description**

Length: 1-1/2", Thickness: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN7765D
Minimum Qty (MOQ):	1 EA
NSN:	4730-00-277-9758
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN776-5D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Overall Length:</b>	1.531 Inches Nominal
<b>Overall Width:</b>	0.813 Inches Nominal
<b>Thickness:</b>	0.750 Inches Nominal
<b>Thread Size:</b>	1/2 In.-20
<b>Thread Provision:</b>	Threaded
<b>Connection Style:</b>	Flared
<b>Bolt Hole Diameter:</b>	0.500 Inches Nominal
<b>Seat Angle In Deg:</b>	37.0
<b>Screw Thread Series Designator:</b>	Unf
<b>Seat:</b>	Included
<b>Fluid Connection Quantity:</b>	1
<b>Fluid Conveyance Type And Size For Which Designed:</b>	5/16 In. Od Tube
<b>Bolt Hole Flats Serrations:</b>	Provided
<b>Bolt Hole Fluid Passage:</b>	Provided
<b>Material:</b>	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6
<b>Material:</b>	Aluminum Alloy 2014
<b>Surface Treatment:</b>	Anodize
<b>Style Designator:</b>	1 Fluid Connection
<b>Surface Treatment:</b>	Anodized, Mil-a-8625, Type 2, Class 2

## How to Order

Order this fitting from our inventory online by visiting <https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.