

**Description**

Length: 2-1/8", Thickness: 1-1/8",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN7768
Minimum Qty (MOQ):	1
NSN:	4730-00-277-9762
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE  
AVAILABLE

## P/N AN776-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Overall Length:</b>	2.031 Inches Minimum And 2.100 Inches Maximum
<b>Overall Width:</b>	1.188 Inches Nominal
<b>Thickness:</b>	1.000 Inches Minimum And 1.125 Inches Maximum
<b>Thread Size:</b>	3/4 In.-16
<b>Thread Provision:</b>	Threaded
<b>Connection Style:</b>	Flared
<b>Bolt Hole Diameter:</b>	0.750 Inches Nominal
<b>Seat Angle In Deg:</b>	37.0
<b>Screw Thread Series Designator:</b>	Unjf
<b>Seat:</b>	Included
<b>Fluid Connection Quantity:</b>	1
<b>Fluid Conveyance Type And Size For Which Designed:</b>	1/2 In. Od Tube
<b>Bolt Hole Flats Serrations:</b>	Provided
<b>Bolt Hole Fluid Passage:</b>	Provided
<b>Material:</b>	Steel, Fed Std 66, Comp 1137
<b>Surface Treatment:</b>	Cadmium And Chromate
<b>Style Designator:</b>	1 Fluid Connection
<b>Surface Treatment:</b>	Cadmium, Qq-p-416, Type 2, Class 2
<b>Specification/standard Data:</b>	88044-an77644j+81343as4875/1 Government Standard

## How to Order

Order this fluid pressure multiple connector from our inventory online by visiting <https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.