

Description

Length: 2-1/8", Thickness: 1-1/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN7768
Minimum Qty (MOQ):	1
NSN:	4730-00-277-9762
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N AN776-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Overall Length:	2.031 Inches Minimum And 2.100 Inches Maximum
Overall Width:	1.188 Inches Nominal
Thickness:	1.000 Inches Minimum And 1.125 Inches Maximum
Thread Size:	3/4 In.-16
Thread Provision:	Threaded
Connection Style:	Flared
Bolt Hole Diameter:	0.750 Inches Nominal
Seat Angle In Deg:	37.0
Screw Thread Series Designator:	Unjf
Seat:	Included
Fluid Connection Quantity:	1
Fluid Conveyance Type And Size For Which Designed:	1/2 In. Od Tube
Bolt Hole Flats Serrations:	Provided
Bolt Hole Fluid Passage:	Provided
Material:	Steel, Fed Std 66, Comp 1137
Surface Treatment:	Cadmium And Chromate
Style Designator:	1 Fluid Connection
Surface Treatment:	Cadmium, Qq-p-416, Type 2, Class 2
Specification/standard Data:	88044-an77644j+81343as4875/1 Government Standard

How to Order

Order this fluid pressure multiple connector from our inventory online by visiting <https://military-fasteners.com/fittings/fluid+pressure+multiple+connectors/AN776-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.