P/N AN7C40A

Description

Fastener Length: 4-1/8", Thread: 7/16-20, Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN7C40A
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-880-1956
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE AVAILABLE

* See page 2 for technical characteristics

P/N AN7C40A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum And 0.703 Inches Maximum
Fastener Length:	4.078 Inches Minimum And 4.125 Inches Maximum
Head Style:	Hexagon
Head Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Between Flats:	0.615 Inches Minimum And 0.627 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	3.422 Inches Minimum And 3.453 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN7C40A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.