

Description

Fastener Length: 4-1/8", Thread: 7/16-20, Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | AN7C40A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-880-1956 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN7C40A Specifications

| | |
|----------------------------------------------|---------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum And 0.703 Inches Maximum |
| Fastener Length: | 4.078 Inches Minimum And 4.125 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.234 Inches Minimum And 0.266 Inches Maximum |
| Width Between Flats: | 0.615 Inches Minimum And 0.627 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 3.422 Inches Minimum And 3.453 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN7C40A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.