

P/N AN8-16

Military-Fasteners.com

#### Description

Fastener Length: 1-7/8", Thread: 1/2-20, Thread Length: 53/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | AN816                                     |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-00-150-9996                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## **P/N AN8-16 Specifications**

| Thread Class:  | 3a   |
|--|--|
| Thread Direction:  | Right-hand   |
| Thread Length:   | 0.750 Inches Minimum And 0.828 Inches Maximum  |
| Fastener Length:   | 1.828 Inches Minimum And 1.875 Inches Maximum  |
| Head Style:  | Hexagon  |
| Head Height:   | 0.265 Inches Minimum And 0.297 Inches Maximum  |
| Width Between Flats:   | 0.740 Inches Minimum And 0.752 Inches Maximum  |
| Shank Unthreaded Hole Diameter:  | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole  |
| Nominal Thread Diameter:   | 0.500 Inches   |
| Grip Length:   | 1.047 Inches Minimum And 1.078 Inches Maximum  |
| Features Provided:   | Finished Head  |
| Thread Quantity Per Inch:  | 20   |
| Minimum Tensile Strength:  | 125000 Pounds Per Square Inch  |
| Hardness Rating:   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| Distance From Head Largest<br>Bearing Surface To Shank Hole<br>Center: | 1.656 Inches Minimum First Hole And 1.688 Inches Maximum First Hole  |
| Material:  | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall   |
| Material Document And<br>Classification:                               | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd<br>Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or<br>Ams 6300 Assn Std 6th Material Response Overall |
| Surface Treatment:   | Cadmium Overall  |
| Surface Treatment Document And<br>Classification:                      | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall   |
| Thread Series Designator:  | Unf  |
|  |  |

# How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN8-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.