

**Description**

length: 2-7/32", grip: 1-7/16", thread: 1/2-20, cadmium plated steel, drilled shank, AN8 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN821                                     |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-00-150-9999                          |
| Schedule B:             | 7318.15.2095                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN8-21 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.750 Inches Minimum And 0.828 Inches Maximum  |
| <b>Fastener Length:</b>   | 2.203 Inches Minimum And 2.250 Inches Maximum  |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.265 Inches Minimum And 0.297 Inches Maximum  |
| <b>Width Between Flats:</b>   | 0.740 Inches Minimum And 0.752 Inches Maximum  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole  |
| <b>Nominal Thread Diameter:</b>   | 0.500 Inches   |
| <b>Grip Length:</b>   | 1.422 Inches Minimum And 1.453 Inches Maximum  |
| <b>Features Provided:</b>   | Finished Head  |
| <b>Thread Quantity Per Inch:</b>  | 20   |
| <b>Minimum Tensile Strength:</b>  | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 2.031 Inches Minimum First Hole And 2.062 Inches Maximum First Hole  |
| <b>Material:</b>  | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| <b>Surface Treatment:</b>   | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>  | Unf  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN8-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.