

P/N AN8-46A

Description

length: 4-27/32", grip: 4-1/16", thread: 1/2-20, cadmium plated steel, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN846A

Minimum Qty (MOQ):

NSN: 5306-00-180-1503

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN8-46A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.782 Inches Minimum
Fastener Length:	4.844 Inches Nominal
Head Style:	Hexagon
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	4.062 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN8-46A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.