

**Description**

tube outer diameter: 3/16", thread: 3/8-24, aluminum, flared tube with bulkhead on run

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                |
|-------------------------|--------------------------------|
| SKU / Model:            | AN804D2                        |
| Minimum Qty (MOQ):      | 1                              |
| NSN:                    | 4730-00-277-5065               |
| ECCN:                   | EAR99                          |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |

NO IMAGE  
AVAILABLE

## P/N AN804D2 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a 1st End Bulkhead   |
| <b>Thread Class:</b>                                  | 3a All Ends   |
| <b>Maximum Operating Temp:</b>                        | -65.0 Deg Fahrenheit 2nd Response                               |
| <b>Maximum Operating Temp:</b>                        | 225.0 Deg Fahrenheit 1st Response                               |
| <b>End Item Identification:</b>                       | Aircraft Application  |
| <b>Connection Style:</b>                              | Flared (tube) All Ends  |
| <b>Leg Length:</b>                                    | 1.390 Inches Minimum 1st End And 1.406 Inches Maximum 1st End   |
| <b>Leg Length:</b>                                    | 0.766 Inches Nominal 2nd End                                    |
| <b>Leg Length:</b>                                    | 0.828 Inches Minimum 3rd End                                    |
| <b>Connection Type:</b>                               | Threaded External Tube All Ends                                 |
| <b>Maximum Operating Pressure:</b>                    | 3000.0 Pounds Per Square Inch Single Response                   |
| <b>Nominal Thread Size:</b>                           | 0.312 Inches 1st End Bulkhead                                   |
| <b>Nominal Thread Size:</b>                           | 0.312 Inches All Ends   |
| <b>Seat Angle:</b>                                    | 37.0 Degrees All Ends   |
| <b>Nominal Outside Diameter Tube Accommodated:</b>    | 0.125 Inches All Ends   |
| <b>Nominal Outside Diameter Tube Accommodated:</b>    | 0.125 Inches 1st End Bulkhead                                   |
| <b>Material:</b>                                      | Aluminum Alloy 2024 Overall Or Aluminum Alloy 2014 Overall      |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Overall                       |
| <b>Media For Which Designed:</b>                      | Hydraulic Fluid 1st Response                                    |
| <b>Media For Which Designed:</b>                      | Oxygen, Gaseous 2nd Response                                    |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf All Ends   |
| <b>Thread Series Designator:</b>                      | Unjf 1st End Bulkhead   |
| <b>Specification/standard Data:</b>                   | 96906-ms24390 Government Standard                               |

## How to Order

Order this tube tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/AN804D2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.