

Description

tube outer diameter: 3/16, thread: 3/8-24, aluminum, 37°, flared tube with bulkhead on run

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN804D3
Minimum Qty (MOQ):	1
NSN:	4730-00-141-9011
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE
AVAILABLE

P/N AN804D3 Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	Flared (tube) All Ends
Leg Length:	1.438 Inches Minimum 1st End And 1.469 Inches Maximum 1st End
Leg Length:	0.828 Inches Nominal 2nd End
Leg Length:	0.891 Inches Nominal 3rd End
Connection Type:	Threaded External Tube All Ends
Nominal Thread Size:	0.375 Inches 1st End Bulkhead
Nominal Thread Size:	0.375 Inches All Ends
Seat Angle:	37.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.188 Inches All Ends
Reduced Passage Nominal Inside Diameter:	0.025 Inches 3rd End
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Fsc Application Data:	Compressor,gas Turbine

How to Order

Order this tee from our inventory online by visiting <https://military-fasteners.com/fittings/tube+tees/AN804D3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.