

Description

tube outer diameter: 1/8", thread: 5/16-24, flared tube, steel, AN806 series plug

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN8062
Minimum Qty (MOQ):	2
NSN:	4730-00-541-4263
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N AN806-2 Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Head Height:	0.174 Inches Nominal
Overall Length:	0.641 Inches Nominal
End Item Identification:	01f Missile, Minuteman Lgm-30
Connection Style:	Flared
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches External
Seat Angle:	37.0 Degrees
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Material Document And Classification:	Qq-s-637 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,tkype 2,class 2 Fed Spec Single Treatment Response Overall
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic
Style Designator:	Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)
Thread Series Designator:	Unjf External
Specification/standard Data:	96906-ms24404 Government Standard

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AN806-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.