

Description

tube outer diameter: 1/8", thread: 5/16-24, flared tube, steel, AN806 series plug

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN8062 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-541-4263 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N AN806-2 Specifications

| | |
|---|---|
| Thread Class: | 3a External |
| Thread Direction: | Right-hand External |
| Head Height: | 0.174 Inches Nominal |
| Overall Length: | 0.641 Inches Nominal |
| End Item Identification: | 01f Missile, Minuteman Lgm-30 |
| Connection Style: | Flared |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch |
| Nominal Thread Size: | 0.312 Inches External |
| Seat Angle: | 37.0 Degrees |
| Material: | Steel Comp 1137 Overall Or Steel Comp 1141 Overall |
| Material Document And Classification: | Qq-s-637 Fed Spec Single Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,tkype 2,class 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | Plug, Tube Fitting Flared (note: Drilled Hole Is Optional Should Not Be Considered As A Separating Characteristic) |
| Style Designator: | Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic) |
| Thread Series Designator: | Unjf External |
| Specification/standard Data: | 96906-ms24404 Government Standard |

How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AN806-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.