

**Description**

outer diameter: 3/4in., thread: 1-1/16-12, 37 degree, flared tube plug, aluminum, AN806 series plug

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AS5168D12](#)

|                         |                                |
|-------------------------|--------------------------------|
| SKU / Model:            | AN806D12                       |
| Minimum Qty (MOQ):      | 2                              |
| NSN:                    | 4730-00-080-3091               |
| ECCN:                   | EAR99                          |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



\* See page 2 for technical characteristics

## P/N AN806D12 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a External   |
| <b>Thread Direction:</b>                              | Right-hand External   |
| <b>Head Height:</b>                                   | 0.341 Inches Nominal  |
| <b>Overall Length:</b>                                | 1.203 Inches Minimum And 1.234 Inches Maximum   |
| <b>lil End Item Identification:</b>                   | Mrap Buffalo Mk2a2  |
| <b>Connection Style:</b>                              | Flared  |
| <b>Thread Quantity Per Inch:</b>                      | 12 External   |
| <b>Nominal Thread Size:</b>                           | 1.062 Inches External   |
| <b>Seat Angle:</b>                                    | 37.0 Degrees  |
| <b>Special Features:</b>                              | Grumman Aerospace Corp Supports A10 Aircraft  |
| <b>Material:</b>                                      | Aluminum Alloy 2014 Or Aluminum Alloy 7075 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-367,t6 Fed Spec 1st Material Response Or Qq-a-367,t73 Fed Spec 2nd Material Response Overall                       |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2,cl 2,blue Mil Spec Single Treatment Response Overall  |
| <b>Style Designator:</b>                              | C42 Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic) |
| <b>Style Designator:</b>                              | Plug, Tube Fitting Flared (note: Drilled Hole Is Optional, Should Not Be Considered As A Separating Characteristic)     |
| <b>Thread Series Designator:</b>                      | Un External   |

## How to Order

Order this threaded tube fitting plug from our inventory online by visiting <https://military-fasteners.com/fittings/threaded+tube+fitting+plugs/AN806D12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.