

Description

tube outer diameter: 1-1/4", thread: 1-5/8-12, aluminum

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AS5169D20](#)

SKU / Model:	AN81420D
Minimum Qty (MOQ):	1
NSN:	5365-00-287-0099
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6



* See page 2 for technical characteristics

P/N AN814-20D Specifications

Thread Class:	3a External
Thread Direction:	Right-hand External
Thread Length:	0.469 Inches Nominal External
Head Height:	0.406 Inches Nominal
Overall Length:	1.000 Inches Nominal
Connection Style:	Plain
Body Core Diameter:	1.078 Inches Nominal
Core Depth:	0.593 Inches Minimum And 0.609 Inches Maximum
Bleeder Hole Center To Threaded End Distance:	0.313 Inches Minimum And 0.375 Inches Maximum
Bleeder Hole Diameter:	0.062 Inches Nominal
Thread Quantity Per Inch:	12 External
Nominal Thread Size:	1.625 Inches External
Seat Angle:	45.0 Degrees
Material:	Aluminum Alloy 2024 Overall Or Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/6,t62 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t581 Fed Spec 1st Material Response Overall Or Qq-a-225/9,t73 Fed Spec 2nd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 1,cl 1 Mil Spec Single Treatment Response Overall
Style Designator:	Plug, Machine W/bleeder Holes
Thread Series Designator:	Un External

How to Order

Order this machine thread plug from our inventory online by visiting <https://military-fasteners.com/fittings/machine+thread+plugs/AN814-20D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.