

P/N AN814-3D

Military-Fasteners.com

### Description

outer diameter: 3/16", thread: 3/8-24, aluminum, AN814 series fitting

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

## Order this part online

### **Additional Information**

#### Alternate Part Numbers

AS5169D03	
SKU / Model:	AN8143D
Minimum Qty (MOQ):	5
NSN:	5365-00-422-5609
ECCN:	9A991.d
National Motor Freight:	013120, Aluminum Article Noi Sub 6



# P/N AN814-3D Specifications

	De Federard	
Thread Class:	3a External	
Thread Direction:	Right-hand External	
Thread Length:	0.265 Inches Nominal External	
Head Height:	0.234 Inches Nominal	
Overall Length:	0.562 Inches Nominal	
Connection Style:	Plain	
Body Core Diameter:	0.125 Inches Nominal	
Core Depth:	0.250 Inches Minimum And 0.266 Inches Maximum	
Bleeder Hole Center To Threaded End Distance:	0.125 Inches Minimum And 0.188 Inches Maximum	
Bleeder Hole Diameter:	0.062 Inches Nominal	
Nominal Thread Size:	0.375 Inches External	
Seat Angle:	45.0 Degrees	
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall	
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall Or Qq-a-225/6,t851 Fed Spec 2nd Material Response Overall	
Surface Treatment:	Anodize Overall	
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall	
Style Designator:	Plug, Machine W/bleeder Holes	
Thread Series Designator:	Unf External	

# How to Order

Order this machine thread plug from our inventory online by visiting <u>https://military-fasteners.com/fittings/machine+thread+plugs/AN814-3D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.