

Description

flared, for hydraulic fluid use

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24392J2](#)

| | |
|-------------------------|---|
| SKU / Model: | AN8152J |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-194-6727 |
| ECCN: | 9A991 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE
AVAILABLE

P/N AN815-2J Specifications

| | |
|---|--|
| Thread Class: | 3a All Ends |
| Maximum Operating Temp: | 225.0 Deg Fahrenheit Single Response |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Nominal Thread Size: | 0.312 Inches All Ends |
| Nominal Overall Length: | 1.219 Inches |
| Material: | Steel Comp 304 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66,aisi 304/sae 30304 Fed Std 1st Material Response Overall Or 66,aisi 316/sae 30316 Fed Std 2nd Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec 1st Treatment Response Inside And Qq-p-35,ty 1 Fed Spec 2nd Treatment Response Inside |
| Style Designator: | Flared W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Furnished Items And Quantity: | 2 Preformed Packing |
| Specification/standard Data: | 88044-an815 Government Standard |

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AN815-2J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.