

# **P/N AN815-2J**

## **Description**

flared, for hydraulic fluid use

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### MS24392J2

SKU / Model: AN8152J

Minimum Qty (MOQ):

NSN: 4730-00-194-6727

ECCN: 9A991

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN815-2J Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Nominal Thread Size:	0.312 Inches All Ends
Nominal Overall Length:	1.219 Inches
Material:	Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66,aisi 304/sae 30304 Fed Std 1st Material Response Overall Or 66,aisi 316/sae 30316 Fed Std 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec 1st Treatment Response Inside And Qq-p-35,ty 1 Fed Spec 2nd Treatment Response Inside
Style Designator:	Flared W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Furnished Items And Quantity:	2 Preformed Packing
Specification/standard Data:	88044-an815 Government Standard

## **How to Order**

Order this boss nipple from our inventory online by visiting <a href="https://military-fasteners.com/fittings/boss+nipples/AN815-2">https://military-fasteners.com/fittings/boss+nipples/AN815-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.