

P/N AN815-3J

Description

tube outer diameter: 3/16", thread: 3/8-24, flared union, male to male corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | AN8153J |
|--------------------|---------|
| Minimum Qty (MOQ): | 1 |

NSN: 4730-00-540-0487

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN815-3J Specifications

| Thread Class: | 3a All Ends |
|--|--|
| Maximum Operating Temp: | -65.0 Deg Fahrenheit 2nd Response |
| Maximum Operating Temp: | 225.0 Deg Fahrenheit 1st Response |
| End Item Identification: | 11f Aircraft, Galaxy C-5 |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.375 Inches All Ends |
| Nominal Overall Length: | 1.218 Inches |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid 1st Response |
| Media For Which Designed: | Oxygen, Gaseous 2nd Response |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Inside |
| Style Designator: | Flared W/ Center Wrenching Facility |
| Thread Series Designator: | Unjf All Ends |
| Furnished Items And Quantity: | 2 Preformed Packing |
| Specification/standard Data: | 88044-an815 Government Standard |
| | |

How to Order

Order this boss nipple from our inventory online by visiting https://military-fasteners.com/fittings/boss+nipples/AN815-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.